



Black & Galvanised Traditional Sheffield Bike Stand

TOTAL Inc. VAT:
\$127.01


*Base price, not including any custom options.

Product Images





Overground Fix




Requires 8xM10
RAWL Expanding
Security Bolts per Bike
Stand (Available in
options)

Overground fixing is ideal for very hard
surfaces e.g. concrete.

Far easier and quicker to install.
we recommend using expanding
M10 RAWL bolts (available).

Underground Fix



Underground fixing is ideal for soft
surfaces e.g. tarmac, block paving,
paving slabs.

Dig a hole 250x250mm and fill with
the bike stand. Then add concrete.



Description

The classic and popular design is perfect for those seeking great value, low maintenance and minimalist bike parking. The shape allows the bike frame & wheel to be securely locked on to the cycle stand.

“They are perfect by the way and you have the best prices by far”

-Jo Oxbury, After The Antique.

Specification

- Mild Steel construction, Galvanised undercoating for rust protection and Polyester Powder Coated RAL 9005 on top, Jet Black.
- Exclusive supplier to Transport for London for secure bike storage and Local Authorities across the UK.
- This bike stand can help contribute towards gaining 2x ENE8 Cycle storage credits when used in the appropriate situation, under the Code for Sustainable Homes
- Overground (boltdown) fixing or Underground (flanged) fixing.
- Overground fixing dimensions: 750mm wide x 750mm tall. Baseplate: 150mm x 150mm with 8 x M12 size holes total. 50mm tube o/d diameter, 2.5mm wall thickness. Approx weight: 8Kg. Unlike most bike stands that only come with 4 bolt holes, the Traditional Sheffield Bike Stand has 8 for added security.
- Underground fixing dimensions: 750mm wide x 1000mm tall. Baseplate: 60mm x 60mm. 50mm tube o/d diameter, 2.5mm wall thickness. Approx weight: 8Kg.
- Recommended spacing of 750mm between each bike stand.

Sheffield Bike Rack Revit / CAD Files

[Download our CAD files](#) or contact us for help with planning. We also have an in-house designer who can check and assist any architect drawings free of charge.

Code: BS1 2122

Fixing bolts: 8 M12 RAWL Bolts required per bike stand (No bolts required for concrete in option)

Finishing: Galvanised and polyester powder coated black (See below for galvanised only version).

[Galvanised Sheffield Stand Product Page](#)

Delivery time: Typically 4 to 5 working days

Additional Information

Best Sellers M2	No
-----------------	----

Choose Fixing	Underground	\$0.00
	Overground fixing including bolts	\$19.97
	Overground	\$5.32



Additional Options