



# The Crossbar Bike Stand


TOTAL Inc. VAT:  
\$344.85

\*Base price, not including any custom options.

## Product Images



### Overground Fix




Requires 8xM10  
RAWL Expanding  
Security Bolts per Bike  
Stand (Available in  
options)

Overground fixing is ideal for very hard  
surfaces e.g. concrete.

For easier and quicker to install,

we recommend using expanding  
M10 RAWL bolts (available).

### Underground Fix



Underground fixing is ideal for soft  
surfaces e.g. tarmac, block paving,  
paving slabs.

Dig a hole 250x250mm and fill with  
the bike stand. Then add concrete.



## Description

A high security bike stand, offering the ability for all cycles and sizes to be locked with both the front wheel and the frame. Also double as a tapping bar if being installed onto public areas.

### Specification

- Mild Steel construction. Stainless Steel option available.
- This bike stand can help contribute towards gaining 2x ENE8 Cycle storage credits when used in the appropriate situation, under the Code for Sustainable Homes
- Underground fixing dimensions: 750mm wide x 1050mm tall. Baseplate: 60mm x 60mm. 50mm tube o/d diameter, 2.5mm wall thickness. Approx weight: 10Kg.

Code: BS6 2152

Delivery time: Typically 3 to 5 working days (up to quantities of 10)

## Additional Information

Best Sellers M2	No
-----------------	----

## Additional Options

Choose Finish	Polyester powdercoated - black	\$0.00
	Mild steel, Galvanised	\$0.00
	Stainless Steel	\$90.75
Choose Fixing	Underground	\$0.00
	Overground	\$6.66
	Overground fixing including bolts	\$27.84

