



Kirby Cycle Stand

TOTAL Inc. VAT:
\$290.40

*Base price, not including any custom options.

Product Images



Description

This is a Sheffield Cycle Stand style variant. The bike stand will accommodate up to two bikes (one each side). The user can lock the wheel and frame to the stand using their own D-lock or chain etc for additional security.

Specification

- Available underground for casting in to the ground or overground for bolting down.
- 48mm overall diameter.
- Wall thickness 3.25mm.
- Underground versions 300mm below ground.
- Height above ground 750mm
- Length Overall 750mm
- Overground versions require 3no 12mm bolts per flange (6 per stand).
- Bolts are available extra.
- Mild steel galvanised to BS EN ISO 1461 (1999).
- Stainless steel is grade 304 as standard.

Installation

Mild steel and stainless steel overground versions, a suitable surface, preferably concrete should already exist for drilling into and bolting down. For underground version a concrete foundation approx. 300mm cube is recommended, depending on ground conditions.

When positioned adjacent to one another stands should be around 800mm apart and around 450mm from any wall or other obstruction.

Delivery time: Typically 14 - 21 days

Additional Information

Best Sellers M2	No
-----------------	----

Additional Options

Cycle Stand Options	Fixed (underground) galvanised	\$0.00
	Fixed (overground) galvanised	\$0.00
	Fixed (underground) stainless steel	\$72.09
	Fixed (overground) stainless steel	\$100.36
Fixing Bolts	No bolts	\$0.00
	6 x 12mm bolts (per stand)	\$15.97

