

Hillmorton Cycle Stand

TOTAL Inc. VAT: \$440.14

*Base price, not including any custom options.

Product Images

BIKEDOCKSOLUTIONS THE MANUFACTURING STANDARD



This is a Sheffield style variant. The stand will accommodate up to two bikes (one each side). The variants like the Model n and Toast Racks offer higher security cycle storage, the user can lock the wheel and frame to the stand using their own Dlock or chain etc.

Specification

- Available ragged for casting in to the ground or flanged for bolting down.
- 48mm overall diameter.
- Wall thickness 3.25mm.
- Ragged versions 300mm below ground.
- Flanged versions require 3 12mm bolts per flange (6 per stand).
- Height above ground 750mm, length overall 750m

Installation

Mild steel and stainless steel flanged versions, a suitable surface, preferably concrete, should already exist for drilling into and bolting down. For ragged ends a concrete foundation approx. 300mm cube is recommended, depending on ground conditions.

When positioned adjacent to one another, stands should be around 800mm apart and around 450mm from any wall or other obstruction.

- Bolts are available extra.
- Mild steel galvanised to BS EN ISO 1461 (1999).
- Stainless steel is grade 304 as standard.
- Other colours available.

Delivery time: 5 - 7 days

Additional Information

Best Sellers M2	No	

Additional Options

Cycle Stand Options	Fixed (overground) galvanised	\$0.00
	Fixed (underground) galvanised	\$0.00
	Fixed (overground) stainless steel	\$144.18
	Fixed (underground) stainless steel	\$115.92
	Fixed (overground) galvanised & plastic coated RAL colour	\$28.27
	Fixed (underground) galvanised & plastic coated RAL colour	\$28.27
Fixing Bolts	No bolts	\$0.00
	6 x 12mm bolts (per stand)	\$14.13

